

**CONTINENTAL™**  
BUILDING PRODUCTS



### Applications

Considerably lighter than traditional 5/8 in. Type X drywall. LiftLite Firecheck 30 reduces labor and speeds up installation time for non-fire-rated applications.

- Interior walls
- Interior ceilings
- Fire-rated for 30-minute wood and steel stud walls

### Advantages

- Considerably lighter
- Reduced installation time
- Enhanced with glass fibers
- Excellent sag resistance
- 99% recycled content by weight
- Less jobsite waste
- Reduced transportation energy
- Low VOC-emitting materials
- Easy score and snap
- Reduced dust

## LIGHTWEIGHT, FIRE-RESISTANT DRYWALL

# LIFTLITE® FIRECHECK® 30

**Continental Building Products** LiftLite Firecheck 30 is a 5/8 in. gypsum board formulated to be considerably lighter than traditional 5/8 in. Type X drywall. This makes it easier to lift, carry and install. Enhanced with glass fibers that provide greater strength, LiftLite Firecheck 30 can be used for both **non-fire-rated** walls and ceilings—saving time and energy with faster installation.

LiftLite Firecheck 30 can be used in building applications that require direct mechanical attachment to wall and ceiling frames composed of wood or metal. It can also be attached to existing surfaces through the use of fasteners or adhesives. Thanks to excellent sag resistance, LiftLite Firecheck 30 may be used with water-based texture application on ceilings with framing up to 24 in. o.c. Additionally, it can be used on walls with framing up to 24 in. o.c. when installed perpendicular to the framing.

While LiftLite Firecheck 30 has some inherent fire-resistant characteristics, this product should not be used to provide the level of fire resistance required by various building codes and standards. For fire resistance, use Continental Firecheck® Type X and Firecheck® Type C products.

LiftLite Firecheck 30 is UL-classified for use in 30-minute single-layer wood- and steel-framed walls, and one-hour double-layer steel framed walls (UL Design W424). When properly sealed and used in a certified sound-rated assembly, LiftLite Firecheck 30 will contribute to required sound transmission classification (STC) values.

Note: LiftLite Firecheck 30 is suitable for interior applications only. It also should not be used where temperatures exceed 125° F for extended periods, or in areas of extreme humidity. In addition, the board should be protected from exposure to adverse conditions during storage and construction.

**LiftLite Firecheck 30 is not a 5/8 in. Type X board. For 5/8 in. Type X board, use 5/8 in. Firecheck Type X.**

JOB NAME: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

DATE: \_\_\_\_\_

## Sustainability

Can contribute to the U.S. Green Building Council's LEED Credit Qualification in several credit categories to assist in obtaining LEED certification.



\*The federal specification for gypsum board, SS-L-30d, was withdrawn in 1984. It is provided here for information only and should not be referenced for new construction.

## Physical Characteristics

**Core:** Non-combustible, dimensionally stable, inert gypsum enhanced with glass fibers for strength and fire resistance

**Paper:** 100% recycled; Front and edges = ivory, back = gray

**Long Edges:** Tapered

**Asbestos free and GREENGUARD certified**

**LEED and Recycled Content:** 99% recycled content, 94% pre-consumer and 5% post-consumer

## Standards and Codes

Formulated to perform in accordance with ASTM C1396/C1396M, Sections 5 and C36; Federal Specification SS-L-30d\*, Type III, Grade R; and CAN/CSA-A82.27-M.

## Technical Specifications

UL classified for surface burning (File No. R16102) (per ASTM E84 and CAN/ULC-S102) Flame spread = 0; Smoke developed = 0; Meeting IBC, Section 803.1, Class A

Core combustibility (per ASTM E136) Non-combustible

UL classified for fire resistance (UL File No. R18482) as Type CLL30 per ASTM E119 and CAN/ULC-S101

## Installation

Install according to Gypsum Association GA-201, GA-216, or ASTM C840. For fire-rated construction, consult GA-600 Fire Resistance Design Manual and UL Fire Resistance Directory Design W424 only. Refer to GA-214 for finishing recommendations.

## Painting and Decorating

For best results, a good gypsum board primer should be applied in accordance with manufacturer's instructions before painting or before any textured material is applied.

## Handling Recommendations

Stack flat, keep dry and lift (do not drag) to avoid scuffing. Avoid damage to edges. For detailed recommendations, refer to GA-216 and GA-801.

## Safety Precautions

Wear safety glasses and NIOSH-approved respirators during cutting, breaking, rasping or other dust-producing activities.

Material Safety Data Sheets (MSDS) are available for all Continental products upon request.

## Available Sizes:


Nominal thickness 5/8 in.

Nominal width 4 ft.

Standard length † 8 ft., 10 ft., 12 ft.

Nominal weight 1.7 lbs./ft.<sup>2</sup> – 1.8 lbs./ft.<sup>2</sup>

†Other lengths available by special order



**CONTINENTAL™**

**CONTINENTAL BUILDING PRODUCTS**

USA (800) 237-5505  
Canada (866) 649-7786  
www.continentalbp.com

